TECHNICAL DATA SHEET



459S 01.11.2014

ANTI-CRATERING ADDITIVE

DESCRIPTION

Anticratering additive specially designed for 2K polyurethane topcoats. Composition based on poly-functional hydrocarbon tensio-active.

PRODUCTS

459S

Anti-cratering Additive

PROPERTIES

- The addition of 459S in the ready-to-spray paint will reduce the surface defects caused by external contamination like oil, greases and silicones.
- Can be used in: Centari[®] 500, Centari[®] 500 HB, Centari[®] 501, Imron[®] 700, 1200S, 679S and 3050S.

RECOMMENDED USE

- Product preparation in accordance to the recommendations in the TDS of the selected quality.
- Addition of maximum 10 ml/l ready-to-spray paint will provide optimum effect.

TECHNICAL DATA SHEET



459S 01.11.2014

ANTI-CRATERING ADDITIVE

EQUIPMENT CLEANING

Use a correct solventborne gunwash.

REMARKS

- Never use in undercoats or basecoats.
- Use only if defect occurs in 1st coat; the systematic use of anticratering additive will sursaturate the environment and create other surface defects.
- Material has to be at room temperature (18-25°C) before use.

SAFETY

This product is classified according to regulation (EC) 1272/2008 (CLP). Consult Safety Data Sheet prior to use. It is strongly recommended to use appropriate personal protection equipment during application. Observe the precautionary notices displayed on the container.

All other products referred to in the paint system build-up are from Cromax[®]. System properties will not be valid when the related material is used in combination with any other materials or additives not belonging to Cromax[®], unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.